

Subway Tile

GLAZED CERAMIC

BEST TILE® / BESTTILE.COM

Memento

COLORS, SIZES & AVAILABILITY

NOMINAL SIZE	FINISH	THICKNESS	GROUT JOINT	BIANCO	MERLETTO	CHIARO DI LUNA	CINERINO	NUVOLA	EDERA	OLTREMARE	BLU DI PRUSSIA
				✓	✓	✓	✓	✓	✓	✓	✓
2.5 x 5	Glossy	9 mm	3/16"	✓	✓	✓	✓	✓	✓	✓	✓
5 x 10.5 Quarter Round	Glossy	NA	3/16"	✓	✓	✓	✓	✓	✓	✓	✓

✓ Stock Item. ⚠ Non-Stock Item. Requires Extra Lead Time.

wTECH INFO

R = Residential, LC = Light Commercial, C = Commercial

ORIGIN: Italy	RECOMMENDED APPLICATIONS	R	LC	C
SHADE VARIATION: V2 - Slight Variation	FLOORS			
WEAR RATING: Class 1 - Wall Applications Only	WALLS / BACKSPLASH	●	●	●
Layout and blend cartons prior to installation.	POOL DECKING			
	EXTERNAL USE - FROST PROOF			

● Approved for this application. * Discuss proper installation method with your Sales Representative.

TILE PERFORMANCE DATA

TECHNICAL FEATURE	NORMS	RESULTS
Water Absorption	ISO 10545-3	> 10 %
Abrasion Resistance (Glazed)	ISO 10545-7	1
Breaking Strength	ISO 10545-4	150 Kg/cm ²
Chemical Resistance - Household Chemicals	ISO 10545-13	Conforms
Chemical Resistance - Low Concentration of Acids and Bases	ISO 10545-13	Conforms
Resistance to Stains	ISO 10545-14	Class 5
Crazing Resistance of Glazed Tiles	ISO 10545-11	Conforms

Always inspect materials prior to installation. Always mix 2-3 cartons at a time while installing to ensure the best blend. All product images are representative only. Variation in color and shading is to be expected. Final selection should be made from actual tile samples.