

Marble Look

GLAZED PORCELAIN

BEST TILE® / BESTTILE.COM

Minas



COLORS, SIZES & AVAILABILITY

| NOMINAL SIZE | FINISH | THICKNESS | GROUT JOINT | BLACK | PEARL |
|-------------------|----------------|-----------|-------------|-------|-------|
| 12 x 24 Rectified | Super Polished | 10.5 mm | 1/8" | ✓ | ✓ |
| 24 x 24 Rectified | Super Polished | 10.5 mm | 1/8" | ✓ | ✓ |
| 24 x 48 Rectified | Super Polished | 10.5 mm | 1/8" | ⌚ | ⌚ |
| 48 x 48 Rectified | Super Polished | 10.5 mm | 1/8" | ⌚ | ⌚ |

✓ Stock Item. ⌚ Non-Stock Item. Requires Extra Lead Time.

TECH INFO

R = Residential, LC = Light Commercial, C = Commercial

| <p>ORIGIN: Spain</p> <p>SHADE VARIATION: V3 - Moderate Variation</p> <p>WEAR RATING: Black: 2 - Walls + Light Residential Floors; Pearl: 3 - Walls + Residential Floors</p> <p>It is not recommended to stagger any tile longer than 15" more than 1/3 the length of the tile.</p> | RECOMMENDED APPLICATIONS | R | LC | C |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------|---|----|---|
| | FLOORS | ● | | |
| | WALLS / BACKSPLASH | ● | ● | ● |
| | POOL DECKING | | | |
| | EXTERNAL USE - FROST PROOF | | | |

● Approved for this application. ★ Discuss proper installation method with your Sales Representative.

TILE PERFORMANCE DATA

| TECHNICAL FEATURE | NORMS | RESULTS |
|------------------------------------------------------------|--------------|-------------------------|
| Water Absorption | ISO 10545-3 | ≤ 0.5% |
| Abrasion Resistance (Glazed) | ISO 10545-7 | 2 / 3 |
| Breaking Strength | ISO 10545-4 | 35-45 N/mm ² |
| Dynamic Coefficient of Friction Wet | AcuTest | 0.21 |
| Dimensions Range | ISO 10545-2 | Conforms |
| Frost Resistance | ISO 10545-12 | Frost Proof |
| Chemical Resistance - Household Chemicals | ISO 10545-13 | A |
| Chemical Resistance - Low Concentration of Acids and Bases | ISO 10545-13 | GLB |
| Resistance to Stains | ISO 10545-14 | Class 5 |
| Resistance to Stains | ISO 10545-11 | Resists |

Always inspect materials prior to installation. Always mix 2-3 cartons at a time while installing to ensure the best blend. All product images are representative only. Variation in color and shading is to be expected. Final selection should be made from actual tile samples.